



SAFETY DATA SHEET

ZINFOS 490 (General colours)

This Safety Data Sheet is prepared in accordance with Annex II to Regulation (EC) No 1907/2006 as amended by Regulations (EU) No. 453/2010 and (EU) 2015/830

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name ZINFOS 490 (General colours)
Product number Z4/GENERAL
Product SUMI code A
Product SUMI version number 1.00

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses An air-drying, liquid, solvent-borne, paint for industrial use. For metal finishing, apply by manual spray. The product may also be applied as a professional coating for structural steelwork in buildings, where it is normally applied by brush and roller unless spray mist can be adequately controlled.

Uses advised against Not for sale to or use by the general public.

1.3. Details of the supplier of the safety data sheet

Supplier Manor Coating Systems Ltd
 Otley Road
 Shipley
 West Yorkshire
 BD17 7DP

Tel: 01274 587351
 Fax: 01274531360
 chiefchemist@manorcoatingsystems.co.uk

Contact person Chief Chemist

1.4. Emergency telephone number

Emergency telephone Manor Coating Systems Ltd. 01274 587351 may be contacted (Office hours only)

National emergency telephone number Members of the public should contact: 111 in UK, 01 809 2166 in Republic of Ireland

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335 STOT RE 2 - H373

Environmental hazards Not Classified

2.2. Label elements

ZINFOS 490 (General colours)

Pictogram



Signal word

Warning

Hazard statements

H226 Flammable liquid and vapour.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.
 H373 May cause damage to organs through prolonged or repeated exposure.
 EUH208 Contains FATTY ACIDS C6 -19-BRANCHED, COBALT (2+) SALTS, BUTANONE OXIME. May produce an allergic reaction.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P260 Do not breathe vapour/ spray.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P284 [In case of inadequate ventilation] wear respiratory protection.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Contains

XYLENE, HYDROCARBONS C9 AROMATICS

Supplementary precautionary statements

P201 Obtain special instructions before use.
 P240 Ground/ bond container and receiving equipment.
 P241 Use explosion-proof electrical equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P261 Avoid breathing vapour/ spray.
 P263 Avoid contact during pregnancy/ while nursing.
 P264 Wash contaminated skin thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P308+P313 IF exposed or concerned: Get medical advice/ attention.
 P312 Call a POISON CENTER/ doctor if you feel unwell.
 P314 Get medical advice/ attention if you feel unwell.
 P321 Specific treatment (see medical advice on this label).
 P332+P313 If skin irritation occurs: Get medical advice/ attention.
 P337+P313 If eye irritation persists: Get medical advice/ attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.
 P391 Collect spillage.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
 P501 Dispose of contents/ container in accordance with national regulations.

Labelling notes

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

2.3. Other hazards

ZINFOS 490 (General colours)

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

XYLENE			10-25%
CAS number: 1330-20-7	EC number: 215-535-7	REACH registration number: 01-2119488216-32-0000	

Classification

Flam. Liq. 3 - H226
Acute Tox. 4 - H332
Skin Irrit. 2 - H315
Eye Irrit. 2 - H319
STOT SE 3 - H335
STOT RE 2 - H373
Asp. Tox. 1 - H304

HYDROCARBONS C9 AROMATICS			1-5%
CAS number: 64742-95-6	EC number: 918-668-5	REACH registration number: 01-2119455851-35-XXXX	

Classification

Flam. Liq. 3 - H226
STOT SE 3 - H335, H336
Asp. Tox. 1 - H304
Aquatic Chronic 2 - H411

ETHYLBENZENE			1-5%
CAS number: 100-41-4	EC number: 202-849-4	REACH registration number: 01-2119489370-35-0000	

Classification

Flam. Liq. 2 - H225
Acute Tox. 4 - H332
STOT RE 2 - H373
Asp. Tox. 1 - H304

2-METHOXY-1-METHYLETHYL ACETATE			0.1 - <1%
CAS number: 108-65-6	EC number: 203-603-9	REACH registration number: 01-2119475791-29-0000	

Classification

Flam. Liq. 3 - H226

ZINFOS 490 (General colours)

2-ETHYL-HEXANOIC ACID, ZIRCONIUM SALT			0.1 - <1%
CAS number: 22464-99-9	EC number: 245-018-1	REACH registration number: 01-2119979088-21-0000	
Classification			
Repr. 2 - H361			
FATTY ACIDS C6 -19-BRANCHED, COBALT (2+) SALTS			0.1 - <1%
CAS number: 68409-81-4	EC number: 270-066-5		
Classification			
Acute Tox. 4 - H302			
Skin Irrit. 2 - H315			
Eye Irrit. 2 - H319			
Skin Sens. 1 - H317			
Repr. 2 - H361f			
Aquatic Chronic 2 - H411			
BUTANONE OXIME			0.1 - <1%
CAS number: 96-29-7	EC number: 202-496-6	REACH registration number: 01-2119539477-28-0000	
Classification			
Acute Tox. 4 - H312			
Eye Dam. 1 - H318			
Skin Sens. 1 - H317			
Carc. 2 - H351			
TRIZINC BIS(ORTHOPHOSPHATE) 90%			1 - 5%
CAS number: 7779-90-0	EC number: 231-944-3		
M factor (Acute) = 1	M factor (Chronic) = 1		
This zinc phosphate is a mixture of zinc phosphate (90%) and non-hazardous additive (10%). Due to the formulation and appropriate test data, commissioned by its supplier, it does not meet the criteria for classification [GHS/CLP part 4.1 of the hazards to aquatic environment as defined in the GHS and CLP regulations]. This mixture must be considered as a whole entity similar to a substance on the basis of test results (OECD 201, 202, 203, 211 and according to GLP protocols)			
Classification			
Aquatic Acute 1 - H400			
Aquatic Chronic 1 - H410			

The full text for all hazard statements is displayed in Section 16.

Composition comments The data shown are in accordance with the latest EC Directives.

Ingredient notes Substances presenting a health or environmental hazard within the meaning of Regulation (EC) No. 1272/2008, assigned a Community workplace exposure limit, classified as PBT/vPvB or included in the Candidate List.

SECTION 4: First aid measures

4.1. Description of first aid measures

ZINFOS 490 (General colours)

General information	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.
Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.
Ingestion	If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.
Skin contact	Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Eye contact	Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	May cause irritation of the respiratory system. In case of overexposure, organic solvents may depress the central nervous system causing dizziness and intoxication, and at very high concentrations unconsciousness and death.
Ingestion	Ingestion may cause nausea, diarrhoea and vomiting.
Skin contact	Xylene is harmful and irritating to skin. Prolonged or repeated contact with skin may cause soreness, irritation or dry skin due to a defatting action.
Eye contact	The liquid splashed in the eyes may cause irritation and reversible damage.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Causes irritation to the skin. This irritation can result in redness and swelling of the skin. Repeated contact with the skin may cause it to become dry and cracked. Causes eye irritation. This irritation can result in redness and swelling of the eyes. May cause respiratory irritation. If inhalation occurs, signs and symptoms may include sore throat, headache, nausea, coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath and may cause transient central nervous system (CNS) depression.
-----------------------------	--

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	recommended: alcohol resistant foam, CO ₂ , powders, water spray/mist
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Vapour is denser than air – flashback may be possible over considerable distances. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required.
-------------------------	--

5.3. Advice for firefighters

Protective actions during firefighting	Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

ZINFOS 490 (General colours)

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Exclude non-essential personnel. Exclude sources of ignition and ventilate the area.
Avoid breathing vapours.
Refer to protective measures listed in sections 7 and 8.

6.2. Environmental precautions

Environmental precautions Vapours are heavier than air. They will spread along the ground and collect in low or confined areas (sewers, basements, tanks). Do not allow to enter drains or watercourses.
If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13).
Clean preferably with a detergent - avoid use of solvents.

6.4. Reference to other sections

Reference to other sections See Section 12 for additional ecological information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

ZINFOS 490 (General colours)

Usage precautions

The Manual Handling Operations Regulations may apply to the handling of containers of this product. To assist employers, the following method of calculating the weight for any pack size is given. Take the pack size volume in litres and multiply this figure by the specific gravity value given in Section 9. This will give the net weight of the coating in kilograms. Allowance will then have to be made for the immediate packaging to give an approximate gross weight. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.

In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded.

Electrical equipment should be protected to the appropriate standard.

Mixture may charge electrostatically: always use earthing leads when transferring from one container to another.

Operators should wear anti-static footwear and clothing and floors should be of the conducting type.

Isolate from sources of heat, sparks and open flame.

Non-sparking tools should be used.

Avoid skin and eye contact.

Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture.

Avoid inhalation of dust from sanding.

Smoking, eating and drinking should be prohibited in application area.

For personal protection see Section 8.

Never use pressure to empty: container is not a pressure vessel.

Always keep in containers of same material as the original one.

Comply with the health and safety at work laws.

Do not allow to enter drains or water courses. Wash hands before eating and before leaving the site.

Remove contaminated clothing and protective equipment before entering eating areas.

Information on fire and explosion protection.

Vapours are heavier than air and may spread along floors.

Vapours may form explosive mixtures with air. Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials, preferably soaked with water, should be stored in purpose-built containers or in metal containers with tight-fitting self-closing lids.

Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Store in accordance with the Dangerous Substances and Explosive Atmospheres Regulations (DSEAR). The requirements are given in the HSE Approved Code of Practice and Guidance, Storage of Dangerous Substances: DSEAR.

The principles contained in the HSE guidance note Chemical Warehousing: The Storage of Packaged Dangerous Substances, should be observed when storing this product. Notes on joint storage.

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

Additional information on storage conditions

Observe label precautions.

Store between 5 and 25 °C in a dry, well ventilated place away from sources of heat and direct sunlight.

Keep container tightly closed.

Keep away from sources of ignition.

No smoking.

Prevent unauthorised access.

Containers which are opened must be carefully resealed and kept upright to prevent leakage.

ZINFOS 490 (General colours)

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³

Sk

HYDROCARBONS C9 AROMATICS

Long-term exposure limit (8-hour TWA): OEL 100 mg/m³

ETHYLBENZENE

Long-term exposure limit (8-hour TWA): WEL 100 ppm 441 mg/m³

Short-term exposure limit (15-minute): WEL 125 ppm 552 mg/m³

Sk

2-METHOXY-1-METHYLETHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 274 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 548 mg/m³

Sk

2-ETHYL-HEXANOIC ACID, ZIRCONIUM SALT

Long-term exposure limit (8-hour TWA): WEL 5 mg/m³

as Zr

Short-term exposure limit (15-minute): WEL 10 mg/m³

as Zr

FATTY ACIDS C6 -19-BRANCHED, COBALT (2+) SALTS

Long-term exposure limit (8-hour TWA): WEL 0.1 mg/m³(Sen)

as Co

BUTANONE OXIME

Long-term exposure limit (8-hour TWA): SUP 10 ppm

Sen

WEL = Workplace Exposure Limit

Sen = Capable of causing occupational asthma.

Sk = Can be absorbed through the skin.

Ingredient comments According to EH40 - List of approved workplace exposure limits. For dust the 8 hour TWA's are:-

Respirable dust 4 mg/cu.m (WEL)

Total inhalable dust 10 mg/cu.m (WEL)

XYLENE (CAS: 1330-20-7)

Biological limit values 650 mmol methyl hippuric acid/mol creatinine in urine. Post shift sampling

ZINFOS 490 (General colours)

DNEL

Industry - Inhalation; Short term systemic effects: 289 mg/m³
 Industry - Inhalation; Long term systemic effects: 77 mg/m³
 Industry - Inhalation; Short term local effects: 289 mg/m³
 Industry - Inhalation; Long term local effects: 77 mg/m³
 Industry - Dermal; Short term systemic effects: 174 mg/m³
 Consumer - Inhalation; Long term systemic effects: 14.8 mg/m³
 Consumer - Inhalation; Short term local effects: 174 mg/m³
 Consumer - Inhalation; Short term systemic effects: 174 mg/m³
 Consumer - Dermal; Long term systemic effects: 108 mg/kg/day
 Consumer - Oral; Long term systemic effects: 1.6 mg/kg/day

PNEC

- Fresh water; 0.327 mg/l
- Marine water; 0.327 mg/l
- Intermittent release; 0.327 mg/l
- Sediment (Freshwater); 12.46 mg/kg
- Sediment (Marinewater); 12.46 mg/kg
- Soil; 2.31 mg/kg
- STP; 6.58 mg/l

HYDROCARBONS C9 AROMATICS (CAS: 64742-95-6)

DNEL

Industry - Inhalation; Long term systemic effects: 150 mg/m³
 Industry - Dermal; Long term systemic effects: 25 mg/kg/day
 Consumer - Inhalation; Long term systemic effects: 32 mg/m³
 Consumer - Dermal; Long term systemic effects: 11 mg/kg/day
 Consumer - Oral; Long term systemic effects: 11 mg/kg/day

PNEC No data available.

ETHYLBENZENE (CAS: 100-41-4)

DNEL

Industry - Inhalation; Long term : 77 mg/m³
 Industry - Inhalation; Short term : 293 mg/m³
 Industry - Dermal; Long term : 180 mg/kg/day
 Consumer - Inhalation; Long term : 15 mg/m³
 Consumer - Oral; Long term : 1.6 mg/kg/day

PNEC

- Fresh water; 0.327 mg/l
- Marine water; 0.327 mg/l
- STP; 6.58 mg/l
- Sediment; 12.46 mg/kg
- Soil; 2.31 mg/kg

2-METHOXY-1-METHYLETHYL ACETATE (CAS: 108-65-6)

DNEL

Industry - Inhalation; Long term systemic effects: 275 mg/kg/day
 Industry - Dermal; Long term systemic effects: 153.5 mg/kg/day
 Consumer - Inhalation; Long term systemic effects: 33 mg/m³
 Consumer - Dermal; Long term systemic effects: 54.8 mg/kg/day
 Consumer - Oral; Long term systemic effects: 1.67 mg/kg/day

ZINFOS 490 (General colours)

PNEC	<ul style="list-style-type: none"> - Fresh water; 0.635 mg/l - Marine water; 0.0635 mg/l - Intermittent release; 6.35 mg/l - STP; 100 mg/l - Sediment (Freshwater); 3.29 mg/kg - Sediment (Marinewater); 0.329 mg/kg - Soil; 0.29 mg/kg
-------------	--

2-ETHYL-HEXANOIC ACID, ZIRCONIUM SALT (CAS: 22464-99-9)

DNEL	<ul style="list-style-type: none"> Industry - Inhalation; Long term systemic effects: 5 mg/m³ Industry - Dermal; Long term systemic effects: 15.75 mg/kg/day Consumer - Inhalation; Long term systemic effects: 2.5 mg/m³ Consumer - Dermal; Long term systemic effects: 7.9 mg/kg/day Consumer - Oral; Long term systemic effects: 7.9 mg/kg/day
PNEC	<ul style="list-style-type: none"> - Fresh water; 0.36 mg/l - Marine water; 0.036 mg/l - Intermittent release; 0.493 mg/l - STP; 71.7 mg/l - Sediment (Freshwater); 6.37 mg/kg - Sediment (Marinewater); 0.637 mg/kg - Soil; 1.06 mg/kg

FATTY ACIDS C6 -19-BRANCHED, COBALT (2+) SALTS (CAS: 68409-81-4)

DNEL	No data available.
PNEC	No data available.

BUTANONE OXIME (CAS: 96-29-7)

DNEL	<ul style="list-style-type: none"> Industry - Inhalation; Long term systemic effects: 9 mg/m³ Industry - Inhalation; Long term local effects: 3.3 Industry - Dermal; Long term systemic effects: 1.3 mg/kg/day Industry - Dermal; Short term systemic effects: 2.5 mg/kg/day Consumer - Inhalation; Long term systemic effects: 2.7 mg/m³ Consumer - Inhalation; Long term local effects: 2 mg/m³ Consumer - Dermal; Long term systemic effects: 0.78 mg/kg/day Consumer - Dermal; Short term systemic effects: 1.5
PNEC	<ul style="list-style-type: none"> - Fresh water; 0.256 mg/l - Intermittent release; 0.118 mg/l - STP; 177 mg/l

TRIZINC BIS(ORTHOPHOSPHATE) 90% (CAS: 7779-90-0)

DNEL	<ul style="list-style-type: none"> Workers - Inhalation; Long term systemic effects: 5 mg/m³ Workers - Dermal; Long term systemic effects: 83 mg/kg bw/day General population - Inhalation; Long term systemic effects: 2.5 mg/m³ General population - Dermal; Long term systemic effects: 83 mg/m³ General population - Oral; Long term systemic effects: 0.83 mg/m³
-------------	--

ZINFOS 490 (General colours)

PNEC

PNECs for zinc: -

- Fresh water; 20.6 µg/L
- Marine water; 6.1 µg/L
- STP; 100 mg/kg, mg/kg dw
- Sediment (Freshwater); 117.8 mg/kg dw
- Sediment (Marinewater); 56.5 mg/kg dw
- Soil; 35.6 mg/kg dw

8.2. Exposure controls

Protective equipment



Safe use of mixture

This Safety Data Sheet should be read in conjunction with the Safe Use of Mixture (SUMI) report referred to in Section 1. The SUMI provides information collated from exposure scenarios of substances relevant to this product and is provided as part of our obligations under REACH Regulations.

Two-pack product protection

Not applicable

Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of solvent vapour below the OEL, suitable respiratory protection must be worn. Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet sanding should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

Personal protection

Requirements for personal protection can only be determined by performing a risk assessment on a case-by-case basis prior to use. This risk assessment should be reviewed regularly.

Eye/face protection

Use safety eyewear, manufactured/tested to EN 166, and designed to protect against splash of liquids.

Hand protection

Use chemical resistant gloves classified under "Standard EN374: Protective gloves against chemicals and micro-organisms" made from Viton or PVA barrier material. The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance and effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact. Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

Hygiene measures

Provide eyewash station. Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

ZINFOS 490 (General colours)

Respiratory protection

Selection of any respiratory protective equipment should ensure that it is adequate to reduce exposure to protect the worker's health and is suitable for the wearer, task and environment, including consideration of the facial features of the wearer.

* Spraying should be undertaken outdoor or in a vented booth. As a minimum, workers should wear a full face respirator to EN140, fitted with a filter suitable for both particulates and vapours, to EN14387, with an assigned protection factor 20 (e.g. A2/P3). A powered full face respirator with combined filter A2/P3 (APF 40) or compressed air breathing apparatus should be worn if used continuously more than 1 hour. Respirators must be worn by anyone in the booth or room during spraying, gun cleaning (spray-to-dry) and throughout the clearance time, until such time as the particulates and solvent vapour concentration have fallen below the appropriate occupational exposure limits.

* Brush or roller applications should be carried out outdoor or in good ventilation areas with 10 to 15 air changes per hour or more. As a minimum, a half face mask respirator with combined filter A2/P3 (APF 20) should be worn. A powered full face respirator with combined filter A2/P3 (APF 40) should be used, if used for more than 1 hour continuously as half face powered respirator are not recommended.

* For other operations: If workers could be exposed to concentration above the exposure limit or where ventilation is poor, they must use a respirator to EN 140, fitted with a filter suitable for both particulates and vapours, to EN 14387, with an assigned protection factor of at least 10 (e.g. A2/P3).

* Enclosed spaces with little or no ventilation: compressed air breathing apparatus should always be worn.

Fit testing and regular servicing is recommended for all respiratory protective equipment. The use of HSE website is strongly recommended in selecting the most appropriate RPE <http://www.healthyworkinglives.com/rpe-selector>

Environmental exposure controls

Refer to the Environmental Protection Act and the Control of Pollution Act. Do not allow to enter drains or water courses.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Viscous liquid.
Colour	Various
Odour	aromatic hydrocarbons
Odour threshold	Not determined.
pH	Not applicable. The product is a non-aqueous mixture.
Melting point	-24°C
Initial boiling point and range	137 - 145°C @ 1013 hPa
Flash point	23 - 32°C SCC (Setaflash closed cup).
Evaporation rate	Not determined.
Flammability (solid, gas)	Material is not a solid or gas
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 1 % Upper flammable/explosive limit: 9 %
Vapour pressure	0.67 kPa @ 20°C
Vapour density	Heavier than air
Relative density	1.35 - 1.45 @ 20°C
Solubility(ies)	Immiscible with water. Soluble in the following materials: Aromatic solvents.

ZINFOS 490 (General colours)

Partition coefficient	Not determined. See Section 12 for partition coefficient data on individual components.
Auto-ignition temperature	465 - 525°C
Decomposition Temperature	Not determined.
Viscosity	400 - 450 mPa•s @ 20°C Rotothinner
Explosive properties	The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.
Oxidising properties	- The product is not expected to be oxidising.
9.2. Other information	
Volatile organic compound	This product contains a maximum VOC content of 440 - 460 g/l. This product contains a maximum VOC content of 31 - 33 g/100 g.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Stable under recommended storage and handling conditions (see section 7). When exposed to high temperatures may produce hazardous decomposition products.
-------------------	--

10.2. Chemical stability

Stability	Stable under recommended storage and handling conditions (see section 7).
------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Keep away from oxidising agents, strongly alkaline and strongly acid materials
---	--

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames, static electricity and other sources of ignition. When exposed to high temperatures may produce hazardous decomposition products.
----------------------------	---

10.5. Incompatible materials

Materials to avoid	Keep away from oxidising agents, strongly alkaline and strongly acid materials
---------------------------	--

10.6. Hazardous decomposition products

Hazardous decomposition products	such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.
---	---

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - dermal

ATE dermal (mg/kg)	4,380.99
---------------------------	----------

Acute toxicity - inhalation

ATE inhalation (gases ppm)	207,874.88
-----------------------------------	------------

ATE inhalation (vapours mg/l)	41.15
--------------------------------------	-------

ATE inhalation (dusts/mists mg/l)	69.29
--	-------

Skin corrosion/irritation

Skin corrosion/irritation	Causes skin irritation.
----------------------------------	-------------------------

Serious eye damage/irritation

ZINFOS 490 (General colours)

Serious eye damage/irritation	Causes serious eye irritation.
<u>Respiratory sensitisation</u>	
Respiratory sensitisation	Based on available data the classification criteria are not met.
<u>Skin sensitisation</u>	
Skin sensitisation	Contains FATTY ACIDS C6 -19-BRANCHED, COBALT (2+) SALTS and 2-BUTANONE OXIME. May produce an allergic reaction
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Based on available data the classification criteria are not met.
Genotoxicity - in vivo	Based on available data the classification criteria are not met.
<u>Carcinogenicity</u>	
Carcinogenicity	Based on available data the classification criteria are not met.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
Reproductive toxicity - development	Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	May cause respiratory irritation.
Target organs	Central nervous system Kidneys Liver
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Target organs	Liver Kidneys
<u>Aspiration hazard</u>	
Aspiration hazard	Based on available data the classification criteria are not met.
General information	
	There are no data available on the mixture itself. The mixture has been assessed following the method according to the "Classification, labelling and packaging of substances and mixtures" EC 1272/2008 and ensuing amendments and classified for toxicological hazards accordingly. See sections 2 and 3 for details.
Inhalation	Exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.
Ingestion	Ingestion may cause nausea, diarrhoea and vomiting.
Skin contact	Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Contains butanoneoxime and fatty acids, C6 -19-branched, Cobalt (2+) salts - may produce an allergic reaction.
Eye contact	Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain. The liquid splashed in the eyes may cause irritation and reversible damage.
Route of entry	This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

ZINFOS 490 (General colours)

Medical symptoms Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.
Solvents may cause some of the above effects by absorption through the skin.

Toxicological information on ingredients.

XYLENE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 3,523.0

Species Rat

ATE oral (mg/kg) 3,523.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 4,200.0

Species Rabbit

ATE dermal (mg/kg) 4,200.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ gases ppmV) 6,700.0

Species Rat

Acute toxicity inhalation (LC₅₀ vapours mg/l) 27.6

Species Rat

Acute toxicity inhalation (LC₅₀ dust/mist mg/l) 10.0

Species Rat

ATE inhalation (gases ppm) 6,700.0

ATE inhalation (vapours mg/l) 27.6

ATE inhalation (dusts/mists mg/l) 10.0

Skin corrosion/irritation

Animal data Dose: 24 and, 72 hours, Rabbit Irritating to skin.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Respiratory sensitisation

Respiratory sensitisation Not sensitising

Skin sensitisation

ZINFOS 490 (General colours)

Skin sensitisation	- Mouse: Not sensitising.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Chromosome aberration: Negative. Ames test: Negative. Gene mutation: Negative.
Genotoxicity - in vivo	Dominant lethal assay, intraperitoneal: Negative.
<u>Carcinogenicity</u>	
Carcinogenicity	NOAEL 500 mg/kg, Oral, Rat, male/female Did not show carcinogenic effects in animal experiments.
IARC carcinogenicity	IARC Group 3 Not classifiable as to its carcinogenicity to humans.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	One-generation study - NOAEL \geq 500 ppm, Inhalation, Rat, male/female P Two-generation study - NOAEL 500 ppm, Inhalation, Rat, male/female P Two-generation study - NOAEL $>$ 500 ppm, Inhalation, male/female F1 Two-generation study - NOAEL $>$ 500 ppm, Inhalation, Rat, male/female F2 This substance has no evidence of toxicity to reproduction.
Reproductive toxicity - development	Maternal toxicity: - NOAEL: 500 ppm, Inhalation, Rat, female
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	May cause respiratory irritation.
Target organs	Central nervous system Liver Kidneys
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	NOAEL 150 mg/kg, (3 months), Oral, Rat NOAEL $>$ 3.5 mg/l, (3 months), Inhalation, Rat, Dog
Target organs	Kidneys Liver
<u>Aspiration hazard</u>	
Aspiration hazard	Aspiration hazard - Category 1 If swallowed accidentally, the product may enter the lungs due to its low viscosity and lead to the rapid development of very serious inhalation pulmonary lesions (medical survey during 48 hours)

HYDROCARBONS C9 AROMATICS

<u>Acute toxicity - oral</u>	
Acute toxicity oral (LD₅₀ mg/kg)	3,492.0
Species	Rat
ATE oral (mg/kg)	3,492.0
<u>Acute toxicity - dermal</u>	
Acute toxicity dermal (LD₅₀ mg/kg)	3,161.0
Species	Rabbit
ATE dermal (mg/kg)	3,161.0
<u>Acute toxicity - inhalation</u>	

ZINFOS 490 (General colours)

Acute toxicity inhalation (LC₅₀ vapours mg/l)	6.193
Species	Rat
<u>Skin corrosion/irritation</u>	
Animal data	Mild skin irritation (rabbit)
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	No eye irritation OECD 405 rabbit
<u>Skin sensitisation</u>	
Skin sensitisation	- Guinea pig: Not sensitising.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Chromosome aberration: Negative. Based on available data the classification criteria are not met.
Genotoxicity - in vivo	Chromosome aberration: Negative. Based on available data the classification criteria are not met.
<u>Carcinogenicity</u>	
Carcinogenicity	Scientifically unjustified.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Fertility: - NOAEC 1500 ppm, Inhalation, Rat P
Reproductive toxicity - development	Developmental toxicity: - NOAEC: 100 ppm, Inhalation, Mouse
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	Vapours may cause drowsiness and dizziness. May cause respiratory irritation.
Target organs	Central nervous system Respiratory system, lungs
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Based on available data the classification criteria are not met.
<u>Aspiration hazard</u>	
Aspiration hazard	Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

ETHYLBENZENE

<u>Skin corrosion/irritation</u>	
Animal data	Dose: 15 mg, 24 hours , Rabbit Slightly irritating.
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Severe eye irritant (500 mg dose)
<u>Aspiration hazard</u>	
Aspiration hazard	Aspiration hazard - Category 1 If swallowed the product may aspirate into the lungs

2-METHOXY-1-METHYLETHYL ACETATE

ZINFOS 490 (General colours)

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 8,532.0

Species Rat

ATE oral (mg/kg) 8,532.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,000.0

Species Rat

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 10.8

Species Rat

Notes (inhalation LC₅₀) LC0 value - no mortality in test. Based on available data the classification criteria are not met.

ATE inhalation (vapours mg/l) 10.8

Skin corrosion/irritation

Animal data Erythema/eschar score: No erythema (0). Oedema score: No oedema (0). Not irritating.

Serious eye damage/irritation

Serious eye damage/irritation Slightly irritating - may cause slight corneal injury

Respiratory sensitisation

Respiratory sensitisation No information available.

Skin sensitisation

Skin sensitisation Guinea pig maximization test (GPMT) - : Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro Ames test: Not mutagenic in AMES Test. Based on available data the classification criteria are not met.

Genotoxicity - in vivo Not determined.

Carcinogenicity

Carcinogenicity NOAEL 300 ppm, Inhalation,

Reproductive toxicity

Reproductive toxicity - fertility Two-generation study - NOAEL 300 ppm, Inhalation, Rat, male/female P Two-generation study - NOAEL 1000 ppm, Inhalation, Rat, male/female F1 Two-generation study - NOAEL 1000 ppm, Inhalation, Rat, male/female F2 Based on available data the classification criteria are not met.

Reproductive toxicity - development Teratogenicity: - NOAEL: 1500 ppm, Inhalation, Rat, female Maternal toxicity: - NOAEL: 1500 ppm, Inhalation, Rat, female Based on available data the classification criteria are not met.

ZINFOS 490 (General colours)

Specific target organ toxicity - single exposure

STOT - single exposure Based on available data the classification criteria are not met.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

2-ETHYL-HEXANOIC ACID, ZIRCONIUM SALT

Skin corrosion/irritation

Animal data Erythema/eschar score: No erythema (0). (rabbit) Oedema score: No oedema (0). (rabbit) Not irritating.

Serious eye damage/irritation

Serious eye damage/irritation Not irritating. (rabbit)

Respiratory sensitisation

Respiratory sensitisation No specific test data are available.

Skin sensitisation

Skin sensitisation Not sensitising. Guinea pig maximisation test Read-across data.

Germ cell mutagenicity

Genotoxicity - in vitro Chromosome aberration: Negative. Read-across data.

Genotoxicity - in vivo Micronucleus test: Negative. Read-across data.

Reproductive toxicity

Reproductive toxicity - fertility One-generation study - NOEL 300 mg/kg/day, Oral, Rat P Read across data

Reproductive toxicity - development Developmental toxicity: - NOEL: 100 mg/kg/day, Oral, Rat Read-across data.
Maternal toxicity: - NOEL: 250 mg/kg/day, Oral, Rat Read-across data.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOEL 3150 - 7080 mg/kg/day, Oral, Rat Read-across data.

BUTANONE OXIME

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 900.0

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 1,000.0

Species Rabbit

Acute toxicity - inhalation

ZINFOS 490 (General colours)

Acute toxicity inhalation (LC₅₀ vapours mg/l)	4.83
Species	Rat
ATE inhalation (vapours mg/l)	4.83
<u>Skin corrosion/irritation</u>	
Animal data	Rabbit 24 hours - abraded and non-abraded skin Not fully reversible in 72 hours Slightly irritating.
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Corrosive eye irritant in rabbits with corneal damage - Category 1(Irreversible).
<u>Skin sensitisation</u>	
Skin sensitisation	Buehler test: - Guinea pig: Sensitising.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	DNA damage and/or repair: Negative. Based on available data the classification criteria are not met.
Genotoxicity - in vivo	Gene mutation:: Negative. Based on available data the classification criteria are not met.
<u>Carcinogenicity</u>	
Carcinogenicity	374 ppm, Inhalation, Rat A liver oncogen in male F-344 rats at a vapor concentration of 374 ppm. NOAEL 54 mg/l, Inhalation, Rat
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Two-generation study - NOAEL >200 mg/kg, Oral, Rat F1
Reproductive toxicity - development	Developmental toxicity: - NOAEL: 200 mg/kg, Oral, Rat

TRIZINC BIS(ORTHOPHOSPHATE) 90%

<u>Acute toxicity - oral</u>	
Acute toxicity oral (LD₅₀ mg/kg)	5,000.1
Species	Rat
ATE oral (mg/kg)	5,000.1
<u>Acute toxicity - inhalation</u>	
Acute toxicity inhalation (LC₅₀ dust/mist mg/l)	5,411.0
Species	Rat
ATE inhalation (dusts/mists mg/l)	5,411.0

SECTION 12: Ecological Information

ZINFOS 490 (General colours)

Ecotoxicity

The mixture has been assessed following the method according to the "Classification, labelling and packaging of substances and mixtures" EC1272/2008 and ensuing amendments and is not classified as dangerous for the environment, but contains substance(s) dangerous for the environment. See section 3 for details.

12.1. Toxicity

Toxicity

There is no toxicity data for the mixture itself.

Ecological information on ingredients.

XYLENE

Acute toxicity - fish	LC ₅₀ , 96 hours: 2.6 mg/l, Onchorhynchus mykiss (Rainbow trout)
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 3.82 mg/l, Daphnia magna
Acute toxicity - aquatic plants	IC ₅₀ , 72 hours: 2.2 mg/l, Freshwater algae
Acute toxicity - microorganisms	EC ₅₀ , 24 hours: 96 mg/l, Bacteria
Chronic toxicity - aquatic invertebrates	NOEC, 48 hours: 6.8 mg/l, Daphnia magna

HYDROCARBONS C9 AROMATICS

Acute toxicity - fish	LC ₅₀ , 96 hours: 9.2 mg/l, Onchorhynchus mykiss (Rainbow trout)
Acute toxicity - aquatic invertebrates	EL50, 48 hours: 3.2 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 72 hours: 2.9 mg/l, Pseudokirchneriella subcapitata
Chronic toxicity - aquatic invertebrates	NOELR, 21 days: 2.14 mg/l, Daphnia magna

ETHYLBENZENE

Acute toxicity - fish	LC ₅₀ , 96 hours: 4.2 mg/l,
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 1.8 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 96 hours: 3.6 mg/l, Pseudokirchneriella subcapitata
Chronic toxicity - aquatic invertebrates	NOEC, 7 days: 1 mg/l, Daphnia magna

2-METHOXY-1-METHYLETHYL ACETATE

Acute toxicity - fish	LC ₁₀₀ , 96 hours: 180 mg/l, Onchorhynchus mykiss (Rainbow trout) NOEC, 96 hours: 100 mg/l, Onchorhynchus mykiss (Rainbow trout)
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 508 - 500 mg/l, Daphnia magna

ZINFOS 490 (General colours)

Acute toxicity - aquatic plants	NOEC, 96 hours: > 1000 mg/l, Selenastrum capricornutum ErC50, 72 hours: >1000 mg/l, Pseudokirchneriella subcapitata
Acute toxicity - microorganisms	EC ₂₀ , 30 minutes: > 1000 mg/l, Activated sludge

2-ETHYL-HEXANOIC ACID, ZIRCONIUM SALT

Acute toxicity - fish	NOELR, 96 hours: >=100 mg/l, Brachydanio rerio (Zebra Fish)
Acute toxicity - aquatic invertebrates	NOEC, 48 hours: 0.17 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 72 hours: 49.3 mg/l, Desmodosmus subspicatus
Acute toxicity - microorganisms	EC ₅₀ , 17 hours: 112.1 mg/l, Pseudomonas putida

BUTANONE OXIME

Acute toxicity - fish	LC ₅₀ , 96 hours: > 100 mg/l, Oryzias latipes (Red killifish)
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: ~ 201 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 72 hours: ~ 11.8 mg/l, Selenastrum capricornutum
Acute toxicity - microorganisms	EC ₅₀ , 17 hours: ~281 mg/l, Pseudomonas putida

TRIZINC BIS(ORTHOPHOSPHATE) 90%

Toxicity	The aquatic toxicity of the zinc phosphate in this mixture was determined in respect of OECD Guidelines 201, 202, 203 and 211 according to Good Laboratory Practices (GLP) protocols. The studies sponsored by the supplier concluded that this mixture is neither of acute ecotoxicity nor chronic ecotoxicity.
-----------------	--

Acute aquatic toxicity

LE(C)₅₀	0.1 < L(E)C ₅₀ ≤ 1
M factor (Acute)	1
Acute toxicity - fish	LC ₅₀ , 96 hours: >100 mg/l, Onchorhynchus mykiss (Rainbow trout)
Acute toxicity - aquatic invertebrates	LC ₅₀ , 48 hours: >100 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 72 hours: >100 mg/l, Pseudokirchneriella subcapitata

Chronic aquatic toxicity

M factor (Chronic)	1
Chronic toxicity - aquatic invertebrates	NOEC, 21 days: >1 mg/l, Daphnia magna

12.2. Persistence and degradability

ZINFOS 490 (General colours)

Persistence and degradability There is no data for the mixture itself.

Ecological information on ingredients.

XYLENE

Persistence and degradability Readily biodegradable

Biodegradation - Degradation % >60: 28 days
Readily biodegradable

HYDROCARBONS C9 AROMATICS

Persistence and degradability The product is readily biodegradable

Phototransformation Scientifically unjustified.

Stability (hydrolysis) Not hydrolysable

Biodegradation Water - Degradation (%) 78%: in 28 days

ETHYLBENZENE

Persistence and degradability The product is readily biodegradable

Biodegradation - Degradation % 66: 10 days

2-METHOXY-1-METHYLETHYL ACETATE

Persistence and degradability Readily biodegradable

Stability (hydrolysis) pH4 - Half-life : 10 days @ 50°C
pH7 - Half-life : 10 days @ 50°C
pH9 - Half-life : 8.1 days @ 25°C
The substance is effectively stable to degradation by hydrolysis .under any environmental conditions likely to be experienced.

Biodegradation Water - Degradation (%) >90%: 28 days
Activated sludge
as inoculum
The substance is readily biodegradable.

2-ETHYL-HEXANOIC ACID, ZIRCONIUM SALT

Phototransformation Water - DT₅₀ : 47.1 hours
Read-across data.

Stability (hydrolysis) Not hydrolysable
Read-across data.

Biodegradation Water - Degradation % 46.54: 10 days
Water - Degradation % 73.82: 28 days

BUTANONE OXIME

ZINFOS 490 (General colours)

Persistence and degradability	The product is readily biodegradable
Stability (hydrolysis)	pH4 - Half-life : <0.3 minute @ °C Hydrolytically unstable at pH4 pH7 - Degradation % 44: 7 days @ 50°C pH9 - Half-life : > 14 days @ 50°C
Biodegradation	Water - Degradation (%) 70%: @ 18 days

12.3. Bioaccumulative potential

Bioaccumulative potential	There is no data for the mixture itself.
Partition coefficient	Not determined. See Section 12 for partition coefficient data on individual components.

Ecological information on ingredients.

XYLENE

Bioaccumulative potential	Not expected to bioaccumulate. BCF: 25.9,
Partition coefficient	log Pow: 3.15

HYDROCARBONS C9 AROMATICS

Bioaccumulative potential	Substance is a UVCB. Standard tests for this endpoint are not appropriate.
Partition coefficient	Not applicable.

ETHYLBENZENE

Bioaccumulative potential	Potential for bioaccumulation is low.
Partition coefficient	log Pow: 3.1 @ 20°C

2-METHOXY-1-METHYLETHYL ACETATE

Bioaccumulative potential	Potential for bioaccumulation is low.
Partition coefficient	log Pow: 1.2 @ 20°C

2-ETHYL-HEXANOIC ACID, ZIRCONIUM SALT

Bioaccumulative potential	log Pow: 2.96, Read-across data.
----------------------------------	----------------------------------

BUTANONE OXIME

Bioaccumulative potential	BCF: 0.5 - 0.6, Cyprinus carpio (Common carp)
----------------------------------	---

12.4. Mobility in soil

Mobility	There is no data on the mobility of the mixture itself.
-----------------	---

Ecological information on ingredients.

XYLENE

Mobility	The product contains volatile solvents which are immiscible with water and will evaporate into the atmosphere. In soil the product has only slight mobility and will partially evaporate
-----------------	--

ZINFOS 490 (General colours)

HYDROCARBONS C9 AROMATICS

Mobility Substance is a UVCB. Standard tests for this endpoint are not appropriate.

ETHYLBENZENE

Mobility The product contains volatile solvents which are immiscible with water and will evaporate into the atmosphere. In soil the product has only slight mobility and will partially evaporate

2-METHOXY-1-METHYLETHYL ACETATE

Mobility Potential for mobility in soil is very high.

Adsorption/desorption coefficient Scientifically unjustified.

2-ETHYL-HEXANOIC ACID, ZIRCONIUM SALT

Henry's law constant 0.294 Pa m³/mol @ 25°C Read-across data.

BUTANONE OXIME

Adsorption/desorption coefficient Water - log Koc: 0.55 @ °C QSAR prediction Negligible adsorption to soil and sediment

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Do not allow to enter drains or water courses.

Disposal methods Waste and emptied containers are controlled wastes and should be disposed of in accordance with The Environment Protection (Duty of Care) Regulations" (in England, Scotland, Wales) or The Controlled Waste (Duty of Care) Regulations (in Northern Ireland).

Waste class The European List of Wastes classification of this product, when disposed of as waste is:
Waste Code: Name of Waste (according to Decision 2000/532/EC):
08 01 11 Waste paint and varnish containing organic solvents or other dangerous substances
If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information contact your local waste authority. Using information provided in this safety data sheet, advice should be obtained from the local waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of empty containers contaminated by the product in accordance with local or national legal provisions.

Additional information

SECTION 14: Transport information

ZINFOS 490 (General colours)

Road transport notes VISCOUS FLAMMABLE LIQUID DEROGATION
In pack sizes less than 450 litres, under the terms of 2.2.3.1.5, this product is not subject to the provisions of ADR.

Sea transport notes VISCOUS FLAMMABLE LIQUID DEROGATION:
In pack sizes up to and including 30 litres, under the terms of 2.3.2.5, this product is not subject to the packaging, labelling and marking requirements of the IMDG Code, but both full documentation and placarding of cargo transport units is still required.

Air transport notes VISCOUS FLAMMABLE LIQUID DEROGATION:
The "viscosity exemption" provision does not apply to air transport.

14.1. UN number

UN 1263

14.2. UN proper shipping name

PAINT

14.3. Transport hazard class(es)

3

ADR/RID classification code 3

ADR/RID label 3

Transport labels



14.4. Packing group

PG III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Transport within the user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of accident or spillage.

EmS F - E, S - E

ADR transport category 3

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

ZINFOS 490 (General colours)

National regulations	<p>The information in this Safety Data Sheet is required pursuant to the provisions of the Health and Safety at Work etc. Act and the Control of Substances Hazardous to Health Regulations which apply to the use of this product at work.</p> <p>The Control of Substances Hazardous to Health Regulations 2002(SI 2002:1689) and amendments.</p> <p>Control of Pollution Act 1974.</p> <p>The Environmental Protection (Duty of Care) Regulations 1992 and amendments</p> <p>The Dangerous Substances & Explosive Atmospheres Regulations 2002(SI 2002:2776).</p> <p>The Manual Handling Operations Regulations 1992, (SI 1992:2793)and amendment, The Stationery Office.</p> <p>The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].</p>
EU legislation	<p>Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).</p> <p>Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).</p> <p>Waste Framework Directive (Directive 2008/98/EC on waste) and amendments</p> <p>Commission Decision 2000/532/EC as amended by Decision 2001/118/EC establishing a list of wastes and hazardous waste pursuant to Council Directive 75/442/EEC on waste and Directive 91/689/EEC on hazardous waste with amendments.</p> <p>ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.</p>
Guidance	<p>COSHH Essentials: easy steps to control chemicals, on-line guidance at http://www.hse.gov.uk/coshh/essentials/index.htm</p> <p>Chemical Warehousing: Storage of Flammable Liquids in Containers, HSG51, HSE</p> <p>Storage: Packaged Dangerous Substances HSG71, HSE.</p> <p>Working with solvents: A guide to safe working practices, INDG273(rev1), HSE</p> <p>Workplace Exposure Limits EH40.</p> <p>Best Practice Guideline 5 "Safe Use of Gloves (June 2010) published by the European Solvents Industry Group (ESIG) available at www.esig.org/en/library/publications/best-practice-guides</p> <p>Control of Substances Hazardous to Health (Fifth Edition) (HSE Books L5)</p> <p>Dangerous Substances and Explosive Atmospheres Regulations 2002, (HSE Books L138)</p> <p>Safe use and handling of flammable liquids HSG140 (Second edition), HSE</p> <p>A step by step guide to COSHH assessment HSG97, HSE</p> <p>BS EN 14042:2003 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents</p>
Paints Directive 2004/42/EC	<p>VOC Content: EU limit for this product (Cat A/i) is: 500 g/litre. This product contains maximum 500 g/litre VOC.</p>

15.2. Chemical safety assessment

SECTION 16: Other information

General information	The product should not be used for purposes other than those shown in Section 1.
Key literature references and sources for data	Raw material supplier's Safety Data Sheets. Reference to ECHA Registered Substance dossiers.
Classification procedures according to Regulation (EC) 1272/2008	Unless indicated elsewhere in this safety data sheet, the classification of this mixture has been determined using a combination of test data, bridging principles and calculation.
Legal obligations	

ZINFOS 490 (General colours)

Revision comments	CLP 1.03 Safe use of mixture information added. This issue replaces CLP 1.02. CLP 1.02 Formulation modified to remove lactation hazard (H362) Revised transport data. Amended information in Section 8. NOTE: Lines within the margin indicate significant changes from the previous revision.
Issued by	Chief Chemist
Revision date	30/11/2017
Revision	CLP 1.03
Supersedes date	16/03/2017
SDS number	20377
Hazard statements in full	H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. H361 Suspected of damaging fertility or the unborn child. H361f Suspected of damaging fertility. H373 May cause damage to organs through prolonged or repeated exposure. H373 May cause damage to organs (Hearing organs) through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. EUH208 Contains FATTY ACIDS C6 -19-BRANCHED, COBALT (2+) SALTS, BUTANONE OXIME. May produce an allergic reaction.

The information of this SDS is based on the present state of our knowledge and on current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The product should not to be used for purposes other than those shown in section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. The information in this safety data sheet does not constitute the user's own assessment of workplace risks as required by other health and safety legislation.

Manor Coating Systems Limited

Safe Use of Mixtures Report



Our SUMI Code: A
Version Number: 1.00
Issue Date: 06/09/2017

Purpose

This Safe Use of Mixtures Report has been compiled from information (including exposure scenarios) that we have received from our suppliers. We are obligated to pass information that is relevant to the safe use of our products (when they are used for their intended purpose and in line with our recommendations shown on our Product Data Sheet) down the supply chain. In general we manufacture mixtures and do not supply substances so we have reviewed the information provided to us and produced this Safe Use of Mixtures Report which should be read in conjunction with the relevant material safety Data Sheet and Product Data Sheet, best practice, process knowledge and guidance notes from the HSE and others when preparing risk assessments and designing safe systems of work. This information is passed down the chain as part of our obligations under REACH.

This report is prepared with our best reasonable endeavour using the information and knowledge in our possession at the date of publication.

SU3 Process Category	PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC10, PROC13, PROC15
SU3 Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated)
SU3 Processes, tasks, activities covered	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities.
SU3 Other Operational Conditions affecting worker exposure	Assumes use at not > 20°C above ambient. Assumes a good basic standard of occupational hygiene is implemented.
SU3 General exposures (closed systems)	Handle substance within a closed system. Film formation - force drying (50 - 100°C). Stoving (>100°C). UV/EB radiation curing. Handle substance within a closed system.
SU3 Mixing operations (closed systems) General exposures (closed systems)	Handle substance within a closed system. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).
SU3 Film formation - air drying	Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).
SU3 Preparation of material for application. Mixing operations (open systems)	Provide a good standard of controlled ventilation (10 to 15 air changes per hour)
SU3 Spraying	Automatic/robotic: Carry out in a vented booth or extracted enclosure. Manual Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Wear a respirator conforming to EN140 with Type A/P2 filter or better.
SU3 Material transfers. Non-dedicated facility	Ensure material transfers are under containment or extract ventilation.
SU3 Material transfers. Dedicated facility	Ensure material transfers are under containment or extract ventilation.
SU3 Roller, spreader, flow application	Provide extract ventilation to points where emissions occur.

SU3 Dipping, immersion and pouring	Provide a good standard of controlled ventilation (10 to 15 air changes per hour).
SU3 Laboratory activities	No other specific measures identified.
SU3 Material transfers. Drum/batch transfers. Transfer from/pouring from containers	Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Wear suitable gloves tested to EN374. Avoid splashing. Clear lines prior to decoupling.
SU3 Production of preparation or articles by tableting, compression, extrusion or pelletisation	Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Wear suitable coveralls to prevent exposure to the skin.
SU3 Equipment cleaning and maintenance	Drain or remove substance from equipment prior to break-in or maintenance.
SU3 Storage	Handle substance within a closed system.
SU22 Process Category	PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15, PROC19
SU22 Processes, tasks, activities covered	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities.
SU22 Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated)
SU22 Other Operational Conditions affecting worker exposure	Assumes use at not > 20oC above ambient. Assumes a good basic standard of occupational hygiene is implemented.
SU22 General exposures (closed systems)	Handle substance within a closed system. Ensure material transfers are under containment or extract ventilation.
SU22 Filling/preparation of equipment from drums or containers. Handle substance within a closed sys	Ensure material transfers are under containment or extract ventilation.
SU22 Preparation of material for application	Handle substance within a closed system. Provide a good standard of controlled ventilation (10 to 15 air changes per hour).
SU22 Film formation - air drying	Indoor: Provide extract ventilation to points where emissions occur. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Outdoor: Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 1 hour. Wear suitable gloves tested to EN374.
SU22 Preparation of material for application.	Indoor: Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Avoid carrying out activities involving exposure for more than 1 hour. Outdoor: Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 1 hour.
SU22 Material transfers. Drum/batch transfers	Transfer via enclosed lines. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Wear suitable gloves tested to EN374. Avoid splashing. Clear lines prior to decoupling.

SU22 Brush, Roller, spreader, flow application	Indoor. Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Wear a respirator conforming to EN140 with Type A/P2 filter or better. Outdoor. Ensure operation is undertaken outdoors. Wear a respirator conforming to EN140 with Type A/P2 filter or better.
SU22 Spraying. Manual	Indoor: Carry out in a vented booth or extracted enclosure. Outdoor: Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374. Wear a respirator conforming to EN140 with Type A/P2 filter or better.
SU22 Dipping, immersion and pouring.	Indoor. Provide extract ventilation to points where emissions occur. Avoid carrying out activities involving exposure for more than 4 hours Outdoor. Ensure operation is undertaken outdoors. Wear a respirator conforming to EN140 with Type A/P2 filter or better.
SU22 Laboratory activitie	Handle in a fume cupboard or under extract ventilation.
SU22 Equipment cleaning and maintenance	Drain down system prior to equipment break-in or maintenance. Avoid carrying out activities involving exposure for more than 4 hours.
SU22 Storage	Handle substance within a closed system. Provide a good standard of controlled ventilation (10 to 15 air changes per hour).

Sectors of Use (SU) and Process Codes (PROC)

Sectors of Use (SU) and Process Codes (PROC) are defined in various regulations.

For the paint industry

SU 3 - Industrial Use of Coatings (eg within a factory on a production line)

SU22 - Use of Coatings by Professional Users (eg a painter and decorator)

Are the most relevant

Method of Preparation

In preparing this Safe Use of Mixtures Report we have relied heavily on the LCID. Specifically contained in Safe Use Information for Mixtures under REACH and the Lead Component (LCID) Methodology - A Brief Description (March 2016) published by CEFIC and their supporting spreadsheets published in 2017.

This approach has been endorsed by the European paint association (CEPE) and the British Coatings Federation (BCF).

The CEFIC approach uses information published by suppliers and in generally available sources including DNELs and PNECs and ECETOC-TRA data.

Further advice, support or assistance

If you require further advice, information, support or assistance please contact us.

Lead Component Identification (LCID) information

LC INHALATION	XYLENE
LC DERMAL	XYLENE
EYE HAZ 1	XYLENE